



A brand of **TOTAL**

## RENAULTMATIC D2



**Fluid for automatic transmissions and hydraulic systems**

### APPLICATIONS

- Special fluid for automatic and hydrostatic transmission systems, recommended for all RENAULT cars and vans.
- Do not use ELF RENAULTMATIC D2 in automatic transmission and power-assisted steering systems of other brands of vehicle.

### APPROVALS

**Manufacturers' approval**

Official manufacturers' approvals: RENAULT

### PERFORMANCES AND CUSTOMER BENEFITS

- Fluid and viscous properties adjusted for the coefficients of friction required for satisfactory clutch operation.
- High viscosity number.
- Very low pour point.
- Advanced protection against wear, corrosion and foaming.
- Excellent thermal and chemical stability.
- Very good compatibility with seals.
- Ensures precision and flexibility of automatic sequences, even at very low speeds and in any weather.

### PHYSICAL AND CHEMICAL CHARACTERISTICS

RENAULTMATIC D2		Method	Value
Density at 15°C	--	ASTM D1298	0.866
Kinematic Viscosity at 40°C	mm <sup>2</sup> /s	ASTM D445	35
Kinematic Viscosity at 100°C	mm <sup>2</sup> /s	ASTM D445	7.0
Flash point Cleveland	-	D92	204
Pour Point	°C	ASTM D97	< -36

*The features mentioned above are average values obtained with some variability in production and do not constitute a specification.*